

ASSMANN DisplayPort Connection Cable

AK-340100-030-S
EAN 4016032288961



DisplayPort connection cable, DP M/M, 3.0m, w/interlock, Ultra HD 4K, bl

This high performance HD digital audio and video cable for example is used to connect a PC or notebook with DisplayPort interface to a monitor with DisplayPort interface.

Ideal for CAD/CAM, GIS, 3D modeling, real time simulation, and more.

- Support up to 4K/2K with 60Hz
- Supported Video Resolution: 4096 x 2160p; 1920 x 1080p
- Connector 1: DP, plug
- Connector 2: DP, plug
- DisplayPort standard: DisplayPort 1.2

- Hoods: molded
- Shielding: triple shielding
- AWG: 28
- Wire material: CU
- Connector surface: nickel-plated
- Interlock: Snap fastener
- Ferrite filter: none
- Color cable: black
- Color connector: black
- Length: 3 m
- Packaging: Polybag
- Assortment: DisplayPort Cables

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	50	8.30	22.00	31.00	55.00	37,510.00
Packaging Unit Inside	10	1.66	7.00	31.00	35.00	7,595.00
Packaging Unit Single	1	0.17	16.00	15.00	3.50	840.00
Net single without Packaging	1	0.12	13.50	13.00	3.00	526.50

More images:

