

DATA SHEET	5550 2460
SILVYN® MPC-M	valid from : 21.12.2015

The SILVYN® MPC M is a polyamide conduit gland for smooth and corrugated conduits.
The hexagonal body with integrated conduit connection enables best assembling.



Material:	PA 66
Features:	Dust protection Moisture protection Tensile strength
Resistance:	To oil
Temperature range	-40°C up to +120°C
Colour	Black (UV-Resistant) Grey (RAL 7001)

Norm Reference:



Notes: Free of halogen, Phosphor and Sulphur

Protection class IP 65 up to IP 68

Dimensions table:

Part No.	Part name	Total length mm	Smallest inner Ø mm	Largest outer Ø mm	Length of thread mm	SW
black						
5550 2460	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2461	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2462	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2463	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2464	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2465	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2469	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2466	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2467	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2468	SILVYN® MPC-M 63x1,5	56	48	76	16	73
grey						
5550 2441	SILVYN® MPC-M 16x1,5/1	38	9	24	11	23
5550 2442	SILVYN® MPC-M 16x1,5/2	40	10,5	28	11	25
5550 2443	SILVYN® MPC-M 20x1,5/1	41	10,5	28	14	25
5550 2444	SILVYN® MPC-M 20x1,5/2	43	14,5	33	14	30
5550 2445	SILVYN® MPC-M 25x1,5	45	19	42	15	37
5550 2446	SILVYN® MPC-M 32x1,5/1	46	24,5	45	16	41
5550 2447	SILVYN® MPC-M 32x1,5/2	48	24,5	48	16	45
5550 2448	SILVYN® MPC-M 40x1,5	59	33	60	16	60
5550 2449	SILVYN® MPC-M 50x1,5	55	39	64	16	60
5550 2439	SILVYN® MPC-M 63x1,5	56	48	76	16	73

DATA SHEET

5550 2460

SILVYN® MPC-M

valid from :
21.12.2015

Suitable

SILVYN® SI
SILVYN® SP
SILVYN® SP-PU
SILVYN® EL waved/smooth
SILVYN® ELU waved/smooth
SILVYN® ELÖ waved/smooth
SILVYN® ELT waved/smooth
SILVYN® ELR smooth

Allocation table:

Conduit	 SILVYN® SI	 SILVYN® SP/ SP-PU	 SILVYN® EL/ELÖ/ELT/ELR/ELU
SILVYN® MPC-M 16x1,5/1	11x14		12
SILVYN® MPC-M 16x1,5/2	13x16	12x16	16
SILVYN® MPC-M 20x1,5/1	13x16	12x16	16
SILVYN® MPC-M 20x1,5/2		16x20	20
SILVYN® MPC-M 25x1,5		22x27	25
SILVYN® MPC-M 32x1,5/1			30
SILVYN® MPC-M 32x1,5/2			32
SILVYN® MPC-M 40x1,5			40
SILVYN® MPC-M 50x1,5			50
SILVYN® MPC-M 63x1,5		49x56	63

For more information please see our current catalogue.

Please do not hesitate to contact our laboratory if there any questions regarding resistance against aggressive agents and special oils.