


U.I. Lapp GmbH	PRODUCT INFORMATION	
	SKINDICHT® BL-M	07.11.2014

For closing pre-threaded holes
Assembling with screwdriver



Corrosion-resistant



Robust



Reliability



Temperature-resistant

Application range

Machine and equipment manufacturing
Electric motor manufacturing

Product Make-up

Metric connection thread acc. to EN 50262

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data


On request:	Fitted with FKM O-ring
Classification:	ETIM 5.0 Class-ID: EC000032 ETIM 5.0 Class-Description: plug for cable screw gland
Material:	Body: nickel-plated brass Sea water-resistant
Protection rating:	IP 54 IP 68 (with O-Ring)
Temperature range:	With O-ring: -30 °C to +100 °C Without O-ring: -60 °C to +200 °C

Product Management	Document: LAPP_PRO1029EN.pdf	1 / 3
--------------------	------------------------------	-------

SKINDICHT® BL-M

07.11.2014

Part number	Article designation / size	Outer Ø (mm)	Pieces / PU
SKINDICHT® BL-M			
52103100	12 x 1,5	14.0	100
52103110	16 x 1,5	18.0	100
52103120	20 x 1,5	22.0	100
52103130	25 x 1,5	28.0	100
52103140	32 x 1,5	35.0	50
52103150	40 x 1,5	44.0	25
52103160	50 x 1,5	54.0	10
52103170	63 x 1,5	70.0	10
SKINDICHT® BL-M with O-ring			
52103105	12 x 1,5	14.0	100
52103115	16 x 1,5	18.0	100
52103125	20 x 1,5	22.0	100
52103135	25 x 1,5	28.0	100
52103145	32 x 1,5	35.0	50
52103155	40 x 1,5	44.0	25
52103165	50 x 1,5	54.0	10
52103175	63 x 1,5	70.0	10
52103190	75 x 1,5	80.0	1

U.I. Lapp GmbH	PRODUCT INFORMATION	 LAPP GROUP
	SKINDICHT® BL-M	07.11.2014



Product Management	Document: LAPP_PRO1029EN.pdf	3 / 3
--------------------	------------------------------	-------