

Miscellaneous cable glands

DIN 46320-C4-Ms with Seal ring No. 6

PG

RoHS



Material Nickel plated brass

Seal ring Soft rubber / Buna-N

Protection IP 54,
with thread seal ring IP 65


Operating Temperature -20 °C – 60 °C (-4 °F – 140 °F) (Soft rubber)
-20 °C – 80 °C (-4 °F – 176 °F) (Buna-N)

Advice:

- Metric thread on request
- Please see page 89 for suitable thread seal ring



- This cable gland is available with additional strain relief (see page 71) and EMC attenuation (see page 72)



AG	\varnothing mm	GL mm	H mm	 mm	Number Soft rubber -20 °C – 60 °C -4 °F – 140 °F	Number Buna-N -20 °C – 80 °C -4 °F – 176 °F
PG 7	6–8	5	15	14/13	1.101.0700.01	1.101.0703.01
PG 9	8–10	6	15	17/15	1.101.0900.01	1.101.0903.01
PG 11	10–12	6	17	20/18	1.101.1100.01	1.101.1103.01
PG 13,5	12–14	6,5	20	22/20	1.101.1300.01	1.101.1303.01
PG 16	14–16	6,5	22	24/22	1.101.1600.01	1.101.1603.01
PG 21	17–19	7	24	30/28	1.101.2100.01	1.101.2103.01
PG 29	26–28	8	26	40/37	1.101.2900.01	1.101.2903.01
PG 36	33–35	9	30	50/47	1.101.3600.01	1.101.3603.01
PG 42	39–41	10	34	57/54	1.101.4200.01	1.101.4203.01
PG 48	45–47	10	37	64/60	1.101.4800.01	1.101.4803.01

➔ Accessories see page 73

DIN 46320-C4-Ms with multiperforated seal ring No. 7

PG

RoHS



Material Nickel plated brass

Seal ring Buna-N (multiperforated)

Protection IP 54,
with thread seal ring IP 65


Operating Temperature -20 °C – 80 °C (-4 °F – 176 °F)

Advice:

- Metric thread on request
- Please see page 89 for suitable thread seal ring



- This cable gland is available with additional strain relief (see page 71) and EMC attenuation (see page 72)



AG	\varnothing mm	GL mm	H mm	 mm	Number
PG 9	4–10	6	15	17/15	1.101.0901.01
PG 11	6,5–12	6	17	20/18	1.101.1101.01
PG 13,5	6,5–13,5	6,5	20	22/20	1.101.1301.01
PG 16	6,5–16	6,5	22	24/22	1.101.1601.01
PG 21	9–20	7	24	30/28	1.101.2101.01
PG 29	17–28	8	26	40/37	1.101.2901.01
PG 36	23–34	9	30	50/47	1.101.3601.01
PG 42	29–40	10	34	57/54	1.101.4201.01
PG 48	35–46	10	37	64/60	1.101.4801.01

➔ Accessories see page 73