

# DIN CABLE GLANDS

## SE (DIN 46320-C4 with EMC attenuation with multiperforated seal ring No. 7)


PG



// Please see page 89 for suitable thread seal ring

Material	Nickel plated brass
Seal ring	Buna-N
Protection	IP 54, with thread seal ring IP 65
Operating Temperature	-20 °C – 80 °C (-4 °F – 176 °F)

RoHS



AG	$\varnothing$ mm	GL mm	H mm	$\varnothing$ mm	E mm	Number
PG 9	4–10	7	17	17 / 15	6	1.680.0906.01
PG 11	6,5–12	7	20	20 / 18	8	1.680.1108.01
PG 13,5	6,5–13,5	8	21	22 / 20	10	1.680.1310.01
PG 13,5	6,5–13,5	8	21	22 / 20	12	1.680.1312.01
PG 16	6,5–16	8	24	24 / 22	12	1.680.1612.01
PG 16	6,5–16	8	24	24 / 22	14	1.680.1614.01
PG 21	9–20	10	27	30 / 28	15	1.680.2115.01
PG 21	9–20	10	27	30 / 28	18	1.680.2118.01
PG 29	17–28	10	30	40 / 37	20	1.680.2920.01
PG 29	17–28	10	30	40 / 37	24	1.680.2924.01

## ZSE (DIN 46320-C4 with EMC attenuation and multiperforated seal ring No. 7 with additional strain relief)


PG



// Please see page 89 for suitable thread seal ring

Material	Nickel plated brass
Seal ring	Buna-N
Protection	IP 54, with thread seal ring IP 65
Operating Temperature	-20 °C – 80 °C (-4 °F – 176 °F)

RoHS



AG	$\varnothing$ mm	GL mm	H mm	$\varnothing$ mm	E mm	Number
PG 9	6,5–10	7	27	17 / 19	6	1.681.0906.01
PG 11	7,5–12	7	29	20 / 22	7	1.681.1107.01
PG 11	7,5–12	7	29	20 / 22	8	1.681.1108.01
PG 13,5	8,5–13,5	8	30	22 / 24	10	1.681.1310.01
PG 13,5	8,5–13,5	8	30	22 / 24	12	1.681.1312.01
PG 16	10,5–16	8	31	24 / 26	12	1.681.1612.01
PG 16	10,5–16	8	31	24 / 26	14	1.681.1614.01
PG 21	13–20	10	36	30 / 33	15	1.681.2115.01
PG 21	13–20	10	36	30 / 33	18	1.681.2118.01
PG 29	19–28	10	40	40 / 42	20	1.681.2920.01
PG 29	19–28	10	40	40 / 42	24	1.681.2924.01