

# EMC CABLE GLANDS


## HSK-M-EMC / HSK-M-PVDF-EMC

## PG, PG-elongated, NPT



|                       |  |
|-----------------------|--|
| Material              | Nickel plated brass  |
| Clamping insert       | Polyamide / PVDF   |
| Seal                  | Buna-N / FKM   |
| O-Ring                | Buna-N / FKM   |
| Protection            | IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)  |
| Operating Temperature | -40 °C – 100 °C (-40 °F – 212 °F) (PA)<br>-35 °C – 150 °C (-31 °F – 302 °F) (PVDF) |

// Other sealing materials e.g. silicone upon request



| AG       | Ø<br>mm | H<br>mm | mm      | GL<br>mm | Number<br>HSK-M-EMC<br>-40 °C – 100 °C | Number<br>HSK-M-PVDF-EMC<br>-35 °C – 150 °C | GL<br>mm | Number<br>HSK-M-EMC elongated<br>-40 °C – 100 °C |
|----------|---------|---------|---------|----------|--|---|----------|--|
| PG 7     | 3–6,5   | 19      | 14      | 5        | 1.691.0700.01                          | 1.698.0700.01                               | 10       | 1.691.0700.60                                    |
| PG 7     | 2–5     | 19      | 14      | 5        | 1.691.0700.15                          | 1.698.0700.15                               | 10       | 1.691.0700.61                                    |
| PG 9     | 4–8     | 21      | 17      | 6        | 1.691.0900.01                          | 1.698.0900.01                               | 10       | 1.691.0900.60                                    |
| PG 9     | 2–6     | 21      | 17      | 6        | 1.691.0900.15                          | 1.698.0900.15                               | 10       | 1.691.0900.61                                    |
| PG 11    | 5–10    | 22      | 20      | 6        | 1.691.1100.01                          | 1.698.1100.01                               | 10       | 1.691.1100.60                                    |
| PG 11    | 3–7     | 22      | 20      | 6        | 1.691.1100.15                          | 1.698.1100.15                               | 10       | 1.691.1100.61                                    |
| PG 13,5  | 6–12    | 24      | 22      | 6,5      | 1.691.1300.01                          | 1.698.1300.01                               | 10       | 1.691.1300.60                                    |
| PG 13,5  | 5–9     | 24      | 22      | 6,5      | 1.691.1300.15                          | 1.698.1300.15                               | 10       | 1.691.1300.61                                    |
| PG 16    | 10–14   | 23      | 24      | 6,5      | 1.691.1600.01                          | 1.698.1600.01                               | 10       | 1.691.1600.60                                    |
| PG 16    | 7–12    | 23      | 24      | 6,5      | 1.691.1600.15                          | 1.698.1600.15                               | 10       | 1.691.1600.61                                    |
| PG 21    | 13–18   | 24      | 30      | 7        | 1.691.2100.01                          | 1.698.2100.01                               | 12       | 1.691.2100.60                                    |
| PG 21    | 9–16    | 24      | 30      | 7        | 1.691.2100.15                          | 1.698.2100.15                               | 12       | 1.691.2100.61                                    |
| PG 29    | 18–25   | 29      | 40      | 8        | 1.691.2900.01                          | 1.698.2900.01                               | 12       | 1.691.2900.60                                    |
| PG 29    | 13–20   | 29      | 40      | 8        | 1.691.2900.15                          | 1.698.2900.15                               | 12       | 1.691.2900.61                                    |
| PG 36    | 22–32   | 35      | 50      | 8        | 1.691.3600.01                          | 1.698.3600.01                               | 15       | 1.691.3600.60                                    |
| PG 36    | 20–26   | 35      | 50      | 8        | 1.691.3600.15                          | 1.698.3600.15                               | 15       | 1.691.3600.61                                    |
| PG 42    | 32–38   | 37      | 57      | 9        | 1.691.4200.01                          |   | 15       | 1.691.4200.60                                    |
| PG 42    | 25–31   | 37      | 57      | 9        | 1.691.4200.15                          |   | 15       | 1.691.4200.61                                    |
| PG 48    | 37–44   | 38      | 64      | 10       | 1.691.4800.01                          |   | 15       | 1.691.4800.60                                    |
| PG 48    | 29–35   | 38      | 64      | 10       | 1.691.4800.15                          |   | 15       | 1.691.4800.61                                    |
| NPT 3/8" | 4–8     | 21      | 17 / 19 | 15       | 1.691.3800.70                          |   |          |  |
| NPT 3/8" | 2–6     | 21      | 17 / 19 | 15       | 1.691.3800.71                          |   |          |  |
| NPT 1/2" | 6–12    | 24      | 22 / 24 | 13       | 1.691.1200.70                          |   |          |  |
| NPT 1/2" | 5–9     | 24      | 22 / 24 | 13       | 1.691.1200.71                          |   |          |  |
| NPT 3/4" | 13–18   | 25      | 30      | 13       | 1.691.3400.70                          |   |          |  |
| NPT 3/4" | 9–16    | 25      | 30      | 13       | 1.691.3400.71                          |   |          |  |