



FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless Connectivity

P/N: DM91

Copyright

© 2017, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: DM91
 Release:
 Commit: 45655
 Language: en-US
 Modified: 2017-10-05
 Formatted: 2017-10-09

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



Part number	DM91
Part name	Industrial TRMS Multimeter with Datalogging and Wireless Connectivity
<p>The FLIR DM91 is an affordable, safe, and reliable digital multimeter for a wide range of electrical and electronic system applications. With its durable design, intuitive user interface, and comprehensive features covering high- and low-voltage applications, the FLIR DM91 is uniquely positioned to help you troubleshoot electrical, electronic, and HVAC/R systems. The FLIR DM91 also has Bluetooth technology, so you can connect via METERLiNK to compatible FLIR infrared cameras, or to mobile devices running the FLIR Tools app.</p>	
<p>Fast and effective troubleshooting:</p> <ul style="list-style-type: none"> • Rich feature set ensures safe and accurate operation. • Diagnose complex systems with high- and low-voltage measurement capabilities. • Measure true RMS, LoZ, and VFD, as well as microamp and milliamp current. • Assess temperatures up to 400°C with the type K thermocouple. • Work safely with the built-in, non-contact AC voltage detector. 	
<p>Work efficiently:</p> <ul style="list-style-type: none"> • Designed and built to make your job easier. • Set up and start working fast owing to an intuitive user interface and enhanced ergonomics. • Work longer with flexible battery options, powerful LED worklights, and a rugged, drop-tested design. • Record results with datalogging and storage of up to 40 000 scalar measurements. • Rely on the protection of CAT IV—600 V, CAT III—1000 V safety ratings. 	
<p>Document and share results:</p> <ul style="list-style-type: none"> • View and share information wirelessly for an improved workflow. • Send readings via METERLiNK to compatible FLIR infrared cameras to embed data into live or saved thermal images. • Wirelessly connect to FLIR Tools or the FLIR InSite workflow management app for streamlined documentation and information sharing. 	
Static datalogging and storage	
Data storage interval, configurable	1–99 seconds
Readings per memory set	40 000
Maximum number of memory sets	1
Connectivity	
Wireless technology	Bluetooth BLE
Communications protocol	METERLiNK



FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless Connectivity

P/N: DM91

© 2017, FLIR Systems, Inc.

#DM91; r. /45655; en-US

Electrical measurement	
Display count	6000
AC/DC V	1000 V AC RMS or 1000 V DC \pm 1%/0.09%
AC/DC mV	600.0 mV \pm 1%/0.5%
VFD AC V	1000 V AC RMS, 45–65 Hz, \pm 1%
AC/DC LoZ V	1000 V AC RMS or 1000 V DC \pm 2.0%
AC/DC A	10.00 A AC RMS or 10.00 A DC \pm 1.5%/1.0%
AC/DC mA range	400.0 mA \pm 1.5%/1.0%
AC/DC μ A range	4000 μ A AC RMS or 4000 μ A DC \pm 1.0%
Frequency counter	100.00 kHz \pm 0.1%
Resistance	6.000 M Ω \pm 0.9%, 50.00 M Ω \pm 3.0%
Continuity check threshold	20–200 Ω
Diode test	1.500 V \pm 0.9%
Capacitance	10.00 mF \pm 1.9%
Temperature, type K thermocouple	–40 to 400°C DMM \pm (1.0% + 3°C)/IGM \pm (1.0% + 5°C) (–40 to 752°F DMM \pm (1.0% + 5.4°F)/IGM \pm (1.0% + 9°F))
Measuring rate	3 samples per second
<i>Accuracy is given as \pm (% of reading)</i>	
Meter data	
Category rating	CAT IV—600 V, CAT III—1000 V
IP rating	IP40
Drop test	3 m (9.8 ft.)
Warranty	Limited lifetime warranty
Calibration cycle	Once per year, recommended
Certifications	
Certifications	C-UL-US, CE, RCM
Safety standards compliance	IEC 61010-1 CAT IV—600 V, CAT III—1000 V
Power system	
Power requirements	3 \times AA alkaline batteries or optional TA04 lithium polymer rechargeable battery system
Battery life, alkaline batteries	Approximately 180 hours with backlight and worklight off
Battery life, TA04 lithium polymer batteries	Approximately 500 hours with backlight and worklight off
Auto power off	Default: 10 minutes
Environmental data	
Operating ambient temperatures and relative humidity (RH)	–10 to 30°C (14–86°F), <85% RH; 30–40°C (86–104°F), <75% RH; 40–50°C (104–122°F), <45% RH
Storage temperature and RH	–20 to 60°C (–4 to 140°F), 0–80% RH (without batteries)
Temperature coefficient	0.1 \times (specified accuracy)/°C, <18°C (64.4°F), >28°C (82.4°F)
Operating altitude	2000 m (6560 ft.)
Pollution degree	2
EMC	EN61326-1



FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless Connectivity

P/N: DM91

© 2017, FLIR Systems, Inc.

#DM91; r. /45655; en-US

Meter physical data	
Weight	535 g (19.8 oz.)
Dimensions (L x W x H)	200 mm x 95 mm x 49 mm (7.9 in. x 3.7 in. x 1.9 in.)
Material	Polycarbonate/ABS
Color	Gray, black, and blue

Shipping information	
Packaging type	Color box with view of product in clamshell
Packaging contents	DM91 FLIR meter, TA82 premium test leads, TA70 alligator clips, TA60 thermocouple probe with adapter, TA84 test lead holder storage/tripod accessory, 3 x AA alkaline batteries, soft carrying case, English-only quick start guide
Packaging weight	1.2 kg (2.6 lb.)
Packaging dimensions (H x W x L)	32 cm x 14 cm x 11 cm (12.6 in. x 5.5 in. x 4.3 in.)
Carton weight	15 kg (33.0 lb.)
Carton dimensions (H x W x L)	65 cm x 30 cm x 56 cm (25.6 in. x 11.8 in. x 22.0 in.)
Carton quantity	12
EAN-13	0793950370919
UPC-12	793950370919
Country of origin	Taiwan
Tariff Ccode	9030310000

Technical support	
Website	http://support.flir.com
E-mail	TMsupport@flir.com
Phone	855-499-3662
Repairs	repair@flir.com

Included in the box	
DM91 Industrial TRMS Multimeter with Datalogging and Wireless Connectivity	
TA82 Premium Silicone Test Leads	
TA84 Test Lead Storage/Tripod Accessory	
TA60 Thermocouple Adapter with Type K Probe	
TA70 CAT IV Insulated Alligator Probes (Slip On)	
Soft-sided carrying case	

Optional accessories	
TA72 Universal Flex Current Probe Accessory 10 in. (25 cm)	
TA74 Universal Flex Current Probe Accessory 18 in. (45 cm)	
TA04-KIT Lithium Polymer Rechargeable Battery Kit	
TA52 Magnet Mount	
TA50 Magnetic Hanging Strap	
TA42 Belt Clip	



FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless Connectivity

P/N: DM91

© 2017, FLIR Systems, Inc.

#DM91; r. /45655; en-US

Optional accessories	
TA10 Protective case for FLIR DMMs	
TA10-F Protective case for FLIR DMMs and TA7X	