

C44P-R, Film, Metallized Polypropylene, AC Filter, 68 uF, 10%, 640 VAC, 1400 VDC



Dimensions

| | |
|---|---------------|
| D | 75mm +/-0.5mm |
| L | 247mm +/-2mm |
| S | 35mm +/-1mm |

Packaging Specifications

| | |
|------------|---------------|
| Mounting: | Bolt - M12x16 |
| Packaging: | Bulk, Bag |

General Information

| | |
|----------------|------------------------------|
| Series: | C44P-R |
| Dielectric: | Metallized Polypropylene |
| Style: | Can |
| Features: | Single Phase PFC |
| RoHS: | Yes |
| Lead: | Threaded Studs M10 |
| Miscellaneous: | Thermal Resistance = 5.3 C/W |

Specifications

| | |
|------------------------|---------------------------|
| Capacitance: | 68 uF |
| Capacitance Tolerance: | 10% |
| Voltage AC: | 640 VAC |
| Voltage DC: | 1400 VDC |
| Temperature Range: | -25/+70°C |
| Rated Temperature: | 70°C |
| Dissipation Factor: | 0.02% 25C |
| Max dV/dt: | 30 V/us |
| Resistance: | 1.634066251 mOhms (10kHz) |
| Ripple Current: | 60 Amps (10kHz 40C) |
| Inductance: | 160 nH |