

C4AF, Film, Metallized Polypropylene, Power, 1.5 μ F, 10%, 350 VAC, 700 VDC, 85°C, Lead Spacing = 27.5mm


General Information

Series:	C4AF
Dielectric:	Metallized Polypropylene
Style:	Radial
Features:	Harsh Environmental Conditions
RoHS:	Yes
Lead:	Wire Leads
Qualifications:	AEC-Q200, IEC61071, EN61071, VDE0560
AEC-Q200:	Yes
Miscellaneous:	Rth = 33 C/W.

Dimensions

L	31.5mm +0.5/-0.7mm
H	28mm +0.2/-0.7mm
T	14mm +0.3/-0.7mm
S	27.5mm +/-0.4mm
LL	6mm +0/-2mm
F	0.8mm +/-0.05mm

Packaging Specifications

Packaging:	Bulk, Box
Packaging Quantity:	96

Specifications

Capacitance:	1.5 μ F
Capacitance Tolerance:	10%
Voltage AC:	350 VAC
Voltage DC:	700 VDC
Temperature Range:	-55/+105°C
Rated Temperature:	85°C
Dissipation Factor:	0.07% MAX
Insulation Resistance:	20 GOhms
Max dV/dt:	115 V/us
Resistance:	8.2 mOhms
Ripple Current:	7.5 Amps Irms (MAX), 173 Amps Ipk
Inductance:	24 nH (ESL)