



Data sheet Product BL 19 141 34

PCB connectors>Female headers


for □ 0.635 mm and Ø up to 0.85 mm - for PC 104 modules, Two rows, 2-72 contacts

Features

grid:	2.54 mm
no. of contacts:	34
contact material:	CuZn-alloy
contact sleeve:	gold-plated
surface contact / contact sleeve:	Ni+≥0.2µm Au
contact spring:	gold-plated
inner contact spring material:	CuBe-alloy
inner contact spring surface:	Ni+0,75µm Au
type internal spring:	6-fingers
plugability for circuit points:	<ul style="list-style-type: none">• □0,55...0,65mm• Ø0,65...0,85mm
insert depth:	2.5...6mm
insertion / drawing force:	1.3N/0.3N
shock resistance:	50 g
volume resistance:	≤10 mΩ
vibration resistance max.:	15 g
capacity between two adjacent contacts:	≤ 0,3 pF
nominal current:	3 A
nominal voltage:	150 V DC
test voltage:	1500 V
insulating body material:	PA 4.6. GF
temperature range:	<ul style="list-style-type: none">• -40°C... +163°C• (260°C/10 s)
class of inflammability:	UL 94 V-0
version:	PC 104

specific insulation resistance:	$>10^7 \Omega \cdot m$
connection type:	THT (soldering)
reflow solderable:	yes

Technical Drawing



A: 14.1 mm

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE

Nottebohmstraße 28
58511 Lüdenscheid

Telefon +49 2351 435-0
Telefax +49 2351 45754

info@fischerelektronik.de
www.fischerelektronik.de