



- 1.CABLE:UL2725,28AWG(7/0.12mm(CCA))x1PAIRS
+24AWG(7/0.2mm(CCA))x2C
INSULATOR:P.P FOR 28AWG&PVC 24AWG
SHIELD:AL-FOIL+DRAIN WIRE+32BRAID(ALM)
JACKET:PVC,COLOR:BLACK,D.D:4.8mm±0.2mm
- 2.CONNECTOR:1 PCS USB A SOLDER TYPE MALE
COLOR:WHITE COLOR
SHELL:NICKEL PLATED
- 3.CONNECTOR:1 PCS USB B SOLDER TYPE MALE
COLOR:WHITE COLOR
SHELL:NICKEL PLATED
- 4.HOOD:MOULDED BLACK COLOR
- 5.Fulfill ROHS Guideline
- 6.ELECTRONIC TEST:100% OPEN SHORT+MISS WIRE TEST

WIRE LIST

P1		P2	
USB A MALE	WIRE COLOR	USB B MALE	AWG
1	RED	1	24AWG
2	WHITE	2	1 PAIRS (28AWG)
3	GREEN	3	
4	BLACK	4	24AWG
SHELL	DRAIN	SHELL	

PART NO	CAB-USB2AB/0.5-BK	SHEET NO	1	THIRD ANGLE PROJECTION	
TITLE:USB A MALE TO USB B MALE L:0.5M,UL2725 CABLE,BLACK COLOR				SCALE	N.T.S
				SIZE	A4
				UNIT	
DWN NO				<input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	
				APPROVED BY & DATE	
				DRAWN BY & DATE	
				CHECKED BY & DATE	