FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人









PANEL CUTOUT
MAX.PANEL THICKNESS
10 mm



Seal Ring



Part Number:LAS2GQF-□■/◎/☆

"□"	Contact structure
11	1NO1NC
22	2NO2NC

"■"	Operation mode
No Letter	Momentary
Z	Latching

"◎"	Crust material
S	Stainless steel
A	Al alloy(black)
N	Nickel Plated Brass

"☆"	IP Class
No Letter	IP40
P	IP65
FP	IP67

SPECIFICATIONS:

1.Switch Rating: AC220V/0.5A, DC110V/0.1A.
2.Mechanical Life: ≥1,000,000cycles.
3.Electrical Life: ≥50,000cycles.
4.Contact Resistance: ≤50mΩ.
5.Insulation Resistance: ≥1,000MΩ.
6.Dielectric Strength: 1,500V, RMS 50Hz, 1min.
7.Operating Temperature: -25˚C～ +55˚C(No Freezing).
8.Operating Force: About 1.2~1.8N(1NO1NC), About 1.4~2N(2NO2NC).
9.Operating Travel: About 2.3mm.
10.Torque: About 0.6Nm max.applied to nut.
11.Protection degree: IP40/IP65/IP67;IK09.
12.Terminal Type: Pin Terminal(1.8 x 0.4mm).

MATERIALS:

1.Contact: Silver alloy.
2.Button: ◎.
3.Body: ◎.
4.Base: PA.

BRAND 品牌 ONPOW

红波按钮制造有限公司
ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

DIMENSIONS	TOLERANCE
0.00 TO 18.00mm	±0.43mm
18.01 TO 30.00mm	±0.52mm
30.01 TO 50.00mm	±0.62mm
50.01 TO 80.00mm	±0.74mm

USED 用途
APPD 审核 CH 2020/04/23
FINISH 处理
CHKD 校对 NCH 2020/04/23
SCALE 比例 1.4 / 1
UNIT 单位 mm
DR. 制图 ZPD 2020/04/23
TITLE 名称 GQ Series Anti-vandal push button
DWG NO. 图号 LAS2GQF
SIZE 图纸 A4
FILE NAME 档案名称 LAS2GQ不带灯.DWG
SHEET 张 1 / 1
REV. 更改 1