FOR 客户名称	APPROVED 客户确认签字	ATTN 销售负责人

The shaded part is illuminated









PANEL CUTOUT
MAX.PANEL THICKNESS
10 mm



Seal Ring





Part Number:GQ22-11WE/△△/▲

"⚠1"	Lamp Color
R	Red
G	Green
Y	Yellow
B	Blue
W	White
O	Orange

"⚠2"	Lamp Color
R	Red
G	Green
Y	Yellow
B	Blue
W	White
O	Orange

"▲"	Lamp Voltage
6V	AC/DC 6V
12V	AC/DC 12V
24V	AC/DC 24V
110V	AC/DC 110V
220V	AC/DC 220V
Other voltage can be made to order	

SPECIFICATIONS:

1.Switch Rating: AC125V/1A, AC250V/0.5A.
2.Mechanical Life: ≥1,000,000cycles.
3.Electrical Life: ≥300,000cycles.
4.Contact Resistance: ≤50mΩ.
5.Insulation Resistance: ≥1,000MΩ.
6.Dielectric Strength: 1,500V, RMS 50Hz, 1min.
7.Operating Temperature: -25℃～ +55℃(No Freezing).
8.Operating Force: About 10N.
9.Operating Travel: About 0.5mm.
10.Torque: About 0.6Nm max.applied to nut.
11.Protection degree: IP67;IK02.
12.Terminal Type: Pin Terminal(2.4 x 0.3mm).

MATERIALS:

1.Contact: Silver alloy.
2.Button: Stainless steel.
3.Body: Stainless steel.
4.Base: PA.

BRAND 品牌 ONPOW

红波按钮制造有限公司
ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD.

DIMENSIONS	TOLERANCE
0.00 TO 18.00mm	±0.43mm
18.01 TO 30.00mm	±0.52mm
30.01 TO 50.00mm	±0.62mm
50.01 TO 80.00mm	±0.74mm

USED 用途		APPD 审核	CH 2020/04/26
FINISH 处理		CHKD 校对	NCH 2020/04/26
SCALE 比例	1. 2 / 1	UNIT 单位	mm
DR. 制图	ZPD 2020/04/26		
TITLE 名称	Micro-travel push button		
DWG NO. 图号	GQ22-11WE	SIZE 图纸	A4
FILE NAME 档案名称	GQ22-11WE .DWG	SHEET 张	1 / 1
REV. 更改	1		