



| | | |
|-------------|--------------------|---------------|
| FOR 客户名称 | APPROVED 客户确认签字 | ATTN 销售负责人 |
| | | |

PANEL CUTOUT
MAX.PANEL THICKNESS
10mm

Part Number:GQ25-□■E/△/▲/◎

LED Pin LED Pin

Contact Composition
1、2、3、4 are one set.
1,2 are normal closed(NC);
3,4 are normal opened(NO).

| "□" | Contact structure |
|-----|-------------------|
| 11 | 1NO1NC |
| 22 | 2NO2NC |

| "■" | Operation mode |
|-----------|----------------|
| No Letter | Momentary |
| Z | Latching |

| "△" | Lamp Color |
|-----|------------|
| R | Red |
| G | Green |
| Y | Yellow |
| B | Blue |
| W | White |

| "▲" | Lamp Voltage |
|------------------------------------|--------------|
| 6V | AC/DC 6V |
| 12V | AC/DC 12V |
| 24V | AC/DC 24V |
| 110V | AC/DC 110V |
| 220V | AC/DC 220V |
| Other voltage can be made to order | |

| "◎" | Crust material |
|-----|-----------------|
| S | Stainless steel |
| A | Al alloy(black) |

MATERIALS:
1.Contact: Silver alloy.
2.Button: ◎.
3.Body: ◎.
4.Base: PA.

SPECIFICATIONS:

- 1.Switch Rating: AC220V/2A, DC220V/0.1A.
- 2.Mechanical Life: ≥1,000,000cycles.
- 3.Electrical Life: ≥50,000cycles.
- 4.Contact Resistance: ≤50mΩ.
- 5.Insulation Resistance: ≥1,000MΩ.
- 6.Dielectric Strength: 1,500V, RMS 50Hz, 1min.
- 7.Operating Temperature: -25℃~ +55℃(No Freezing).
- 8.Operating Force: About 5N(1NO1NC)/About 7.5N(2NO2NC).
- 9.Operating Travel: About 2.5mm.
- 10.Torque: About 0.6Nm max.applied to nut.
- 11.Protection degree: IP65,IP67(Momentary can made to order);IK10.
- 12.Terminal Type: Pin Terminal(2.8 x 0.5mm).

| | | | |
|--|--|--|--------------------------|
| BRAND 品牌 ONPOW | | 红波按钮制造有限公司 ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. | |
| USED 用途 THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. AND SHALL NOT BE REPRODUCED COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ONPOW PUSH BUTTON MANUFACTURE CO.,LTD. | | APPD 审核 CH 2020/03/04 | |
| FINISH 处理 | | CHKD 校对 NCH 2020/03/04 | |
| SCALE 比例 1.1 / 1 | | UNIT 单位 mm | DR. 制图 ZPD 2020/03/04 |
| DIMENSIONS TOLERANCE 0.00 TO 18.00mm ±0.43mm 18.01 TO 30.00mm ±0.52mm 30.01 TO 50.00mm ±0.62mm 50.01 TO 80.00mm ±0.74mm | | TITLE 名称 GQ Series Anti-vandal push button | |
| DWG NO. 图号 GQ25-E | | SIZE 图纸 A4 | |
| FILE NAME 档案名称 GQ25-E.DWG | | SHEET 张 1 / 1 | REV. 更改 1 |