


## V-N-FS

metr.



**Materiał** poliamid

**Stopień ochrony** IP 54

**Temperatura ciągłej pracy** -40 °C – 100 °C

**Kolory** szary (RAL 7035), czarny (RAL 9005)




**Uwagi:**  
- Inne kolory na zapytanie

AG	GL mm	H mm	D mm	nr zamów. PA szare	nr zamów. PA czarne
M 12 x 1,5	6	10	15	1.251.1200.50	1.251.1201.50
M 16 x 1,5	7	11,5	20	1.251.1600.50	1.251.1601.50
M 20 x 1,5	6	9,5	25	1.251.2000.50	1.251.2001.50
M 25 x 1,5	11	15,5	30	1.251.2500.50	1.251.2501.50
M 32 x 1,5	11	16	38	1.251.3200.50	1.251.3201.50
M 40 x 1,5	13	18	46	1.251.4000.50	1.251.4001.50
M 50 x 1,5	13	18,5	56	1.251.5000.50	1.251.5001.50
M 63 x 1,5	15	19	69	1.251.6300.50	1.251.6301.50

## V-N-FS

PG



**Materiał** poliamid

**Stopień ochrony** IP 54

**Temperatura ciągłej pracy** -40 °C – 100 °C

**Kolory** szary (RAL 7035), czarny (RAL 9005)



**Uwagi:**  
- Inne kolory na zapytanie

AG	GL mm	H mm	D mm	nr zamów. PA szare	nr zamów. PA czarne
PG 7	6	8	15	1.251.0700.11	1.251.0701.11
PG 9	6	9	19	1.251.0900.11	1.251.0901.11
PG 11	6	9	22	1.251.1100.11	1.251.1101.11
PG 13,5	6	9,5	25	1.251.1300.11	1.251.1301.11
PG 16	6	9,5	27	1.251.1600.11	1.251.1601.11
PG 21	8	11	33	1.251.2100.11	1.251.2101.11
PG 29	8	12	44	1.251.2900.11	1.251.2901.11
PG 36	10	15	55	1.251.3600.11	1.251.3601.11
PG 42	10	16	62	1.251.4200.11	1.251.4201.11
PG 48	12	16	69	1.251.4800.11	1.251.4801.11