

## Scheda di prodotto / Product Datasheet

Products type: wireless charging emitter			Model No: QICHARSUP2C10W-01
Line	Parameter	Value	Remarks
1	Technical standard	WPC	
2	Range of application	All wireless charger for RX with Qi standard	
3	Coil quantity	2 Coils	
4	Charging type	Electro-magnetic induction	
5	Charging style	one to one in active area	
6	Charging active area	L*W = 69*32mm	
7	Charging distance	3-8mm	Distances is between RX coil and TX coil
8	Charging temperature	<45°C	
9	Working frequency	110KHZ ~ 205KHZ	
10	Power input	5V/2.0A for 5W output 9V/1.8A for 10W output	
11	Power output	Output power automatic adjustment based on battery power and maximum up to 5 Watts or 10W for fast charge phones (must use QC 2.0 or 3.0 cigarette lighter plug)	
12	Conversion rate	75%	Power output average value
13	Over-voltage protection	Over-voltage protection for 10V	
14	Over-discharge protection	Over-current protection for 1.8A	
15	Product size	132(L) x910 (W) x 26(H) mm	
16	Net weight	113g	
17	Accessories	User manual, power cable, cigarette lighter plug, bracket, air vent clip	



Per.Pic. Technik Kabel will reserve to make technical changes to the device without notice.

All installation work must be performed by a qualified professional installer only. The manufacturer / dealer is not liable for any kind of incidental or indirect damages.

Document Revision: 0 - 27.03.2018