









REV	ECN	DESCRIPTION	DRFT	DATE
-----	-----	-------------	------	------



- XX: 150~1500mm  
15: 150±15mm  
30: 300±20mm  
50: 500±20mm  
A0: 1000±40mm  
A5: 1500±40mm  
Wire Length(L): 150~1500mm

1. Rated voltage/current : 3pin: 60V / 3A  
4pin: 60V / 3A  
5pin: 30V / 3A  
6pin: 30V / 1.5A  
8pin: 30V / 1.5A
2. Withstanding voltage : 3,4pin: AC850V/1Min  
5,6,8pin: AC650V/1Min
3. Levels of protection: IP67
4. Wire specifications :  
3pin: 24AWG/0.25mm<sup>2</sup>, UL1061  
4pin: 24AWG/0.25mm<sup>2</sup>, UL1061  
5pin: 24AWG/0.25mm<sup>2</sup>, UL1061  
6pin: 26AWG/0.14mm<sup>2</sup>, UL1061  
8pin: 26AWG/0.14mm<sup>2</sup>, UL1061
5. Wire connection mode: soldering
6. Operating temperature: -25°C ~ +80°C
7. For Panel Thickness Range: 2.0 ~ 3.5mm
8. RoHS Compliance

3pin A Coding		4pin A Coding		5pin B Coding		6pin A Coding		8pin A Coding	
 <p>Pin Assignment Front View</p>		 <p>Pin Assignment Front View</p>		 <p>Pin Assignment Front View</p>		 <p>Pin Assignment Front View</p>		 <p>Pin Assignment Front View</p>	
								8	Red
								7	Blue
						6	Pink	6	Pink
				5	Gray	5	Gray	5	Gray
4	Black	4	Black	4	Black	4	Black	4	Yellow
3	Blue	3	Blue	3	Blue	3	Blue	3	Green
		2	White	2	White	2	White	2	Brown
1	Brown	1	Brown	1	Brown	1	Brown	1	White
Pin	Wire Color	Pin	Wire Color	Pin	Wire Color	Pin	Wire Color	Pin	Wire Color
Pin Out		Pin Out		Pin Out		Pin Out		Pin Out	

DETACHED LISTS	PART NO.: SDM8XXXPMMSH7BXX00AH		 宁波高松电子有限公司 NINGBO DEGSON ELECTRICAL CO., LTD	
	APPD:		NAME: SD-M8X-XXP-MM-SH7BXX-00A(H)	
	CHKD:			
	DRFT: LZ 2018.09.07		TITLE: CUSTOMER DRAWING	
			REV D0-1	
	 THIRD ANGLE PROJECTION		DRAWING NO.: XXXXXXX-XX-CXX	
			SHEET 1/1	
			DO NOT SCALE DRAWING	
			SCALE 1:1	