

# End clamp - CLIPFIX 35

3022218

<https://www.phoenixcontact.com/pc/products/3022218>



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.

---

Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, width: 9.5 mm, color: gray



---

## Your advantages

- Large-surface labeling
- Design width of just 9.5 mm
- Phoenix Contact has engineered its CLIPFIX end brackets to maintain a secure grip on the various DIN rail systems

# End clamp - CLIPFIX 35

3022218

<https://www.phoenixcontact.com/pc/products/3022218>



## Commercial Data

Item number	3022218
Packing unit	50 pc
Minimum order quantity	50 pc
Product Key	BE7111
Catalog Page	Page 538 (C-3-2019)
GTIN	4017918156541
Weight per Piece (including packing)	5.254 g
Weight per Piece (excluding packing)	5.1 g
Customs tariff number	39269097
Country of origin	PL

# End clamp - CLIPFIX 35

3022218

<https://www.phoenixcontact.com/pc/products/3022218>




## Technical Data

### Product properties

Product type	End block
--------------	-----------

### Dimensions

Dimensional drawing	
Width	9.5 mm
Height NS 35/7,5	35.5 mm
Length	55.6 mm

### Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V2
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Relative insulation material temperature index (Elec., UL 746 B)	125 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 2
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 2

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

### Mounting

Mounting type	NS 35/7,5
	NS 35/15

# End clamp - CLIPFIX 35

3022218

<https://www.phoenixcontact.com/pc/products/3022218>



Phoenix Contact 2022 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)