



NOTE 1. After the vertical mating of the adapter (MS-180-HRMJ-1) and the receptacle (MS-180) is completed, adjust the fixture stop and the load force to within 6 to 10 N.

6	BERYLLIUM COPPER	GOLD PLATING	12	STAINLESS STEEL	
5	BERYLLIUM COPPER	GOLD PLATING	11	STAINLESS STEEL	
4	BERYLLIUM COPPER	GOLD PLATING	10	STAINLESS STEEL	
3	BERYLLIUM COPPER	NICKEL PLATING	9	PTFE	
2	BERYLLIUM COPPER	GOLD PLATING	8	PTFE	
1	STAINLESS STEEL	GOLD PLATING	7	PTFE	
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 5 : 1	COUNT		DESCRIPTION OF REVISIONS
DESIGNED		CHECKED		DATE	
APPROVED : KY. SHIMIZU		09.07.01		DRAWING NO. EDC3-180888-00	
CHECED : TY. OZAKI		09.07.01		PART NO. MS-180-HRMJ-1	
DESIGNED : TS. NAKAGAWA		09.06.24		CODE NO. CL358-0285-4-00	
DRAWN : TS. NAKAGAWA		09.06.24		1/1	