

Housing cover - EH 67,5-C DS/ABS BK9005 - 2201517

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Component housing, connection opening on both sides, Upper part, color: black, width: 67.5 mm

Why buy this product

- ✓ Item is part of the EH product range
- ✓ Tool-free mounting
- ✓ Available in overall widths from 22.5 mm ... 90 mm
- ✓ Inflammability class HB acc. to UL 94
- ✓ Variety of connection technologies
- ✓ Can be mounted on the DIN rail or the wall

RoHS

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 046356 832083
GTIN	4046356832083
Weight per Piece (excluding packing)	24.200 g
Custom tariff number	85389099
Country of origin	India

Technical data

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C (depending on power dissipation)
---------------------------------	---

Dimensions

Width	67.5 mm
-------	---------

Housing cover - EH 67,5-C DS/ABS BK9005 - 2201517

Technical data

Standards and Regulations

Flammability rating according to UL 94	HB
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Classifications

eCl@ss

eCl@ss 4.0	27180401
eCl@ss 4.1	27180401
eCl@ss 5.0	27180506
eCl@ss 5.1	27180506
eCl@ss 6.0	27180802
eCl@ss 7.0	27182702
eCl@ss 8.0	27182702
eCl@ss 9.0	27182702

ETIM

ETIM 3.0	EC001031
ETIM 4.0	EC001031
ETIM 5.0	EC001031
ETIM 6.0	EC001031

UNSPSC

UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501
UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501

Accessories

Accessories

Filler plug

Filler plugs - EH 22,5-FP/ABS BK9005 - 2201842



Component housing, color: black, width: 22.5 mm

Housing cover - EH 67,5-C DS/ABS BK9005 - 2201517

Accessories

Filler plugs - EH 22,5-FP/ABS GY7035 - 2201843



Component housing, color: gray, width: 22.5 mm

Necessary add-on products

PCB terminal block - MKDS 3/12-5,08 - 1714308



PCB terminal block, nominal current: 24 A, nom. voltage: 400 V, pitch: 5.08 mm, number of positions: 12, connection method: Screw connection with tension sleeve, mounting: Wave soldering, conductor/PCB connection direction: 0 °, color: green. The article can be aligned to create different nos. of positions!

Header - MSTBV 2,5/12-G - 1753631



PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 12, pitch: 5 mm, color: green, contact surface: Tin, mounting: Wave soldering

Header - MSTBV 2,5/12-G-5,08 - 1758115



PCB headers, nominal current: 12 A, rated voltage (III/2): 320 V, number of positions: 12, pitch: 5.08 mm, color: green, contact surface: Tin, mounting: Wave soldering